



**benair**

## **Window Type Air Conditioner**

*Elegant!*

*Compact!*

*Durable!*

*Keep Cool! Feel Cool!*



*Convenient Living Environment*

SPECIFICATIONS	MODEL	CW09	CW12	CW18	CW24	CW28
CAPACITY -COOLING	BTU/ HR	9000	12000	18200	24250	28000
CAPACITY -ELE.HEATING (HE)	K.W.	2	2	3	3	3
CAPACITY -HEATING (HP)	BTU/ HR	10000	14000	20000	27000	30500
POWER SUPPLY	VOLTS / PH / HZ	220-240V-1 PH/50				
POWER LOAD (COOLING)	AMP	6.5	8.2	9.8	12	14.7
AIR FLOW	CFM	300	350	550	550	600
MOISTURE REMOVAL	LTR / HR	1.1	1.7	2.7	2.6	3.1
FAN SPEED	COOLING	3 STEPS				
	HEATING	2 STEPS				
REFRIGERANT	FREON	R-22				
DIMENSION (MM)	HEIGHT	368	368	457	457	432
	WIDTH	520	520	673	673	698
	DEPTH	673	673	736	736	876
WEIGHT	KG	34	41	74	78	90

## ENGINEERING FEATURES

### CABINET

Every cabinet is made of rust and corrosion resistant galvanized steel and Powder coated epoxy finish. Your unit will last for years even in harsh weather.

### GROOVED COPPER TUBING

Grooved copper tubing helps maximize the efficiency of the cooling process by exposing more of the inner tube surface to the refrigerant, thus increasing heat transfer.

### COMPRESSOR

Energy efficient powerful inertia compressor is internally overload protected.

### CAPACITOR

Individually connected capacitor for compressor and fan motor.



\*Optional Model With Remote Control

### VENTILATION CONTROL

To freshen the room by discharging stale room air, slide the control to open. To circulate the air in the room, slide it to close.

### ONE-TOUCH AIR FILTER

You can slide the filter in and out without removing the front grill, for quick easy cleaning.

### 4-WAY AIR DEFLECTION SYSTEM

The adjustable front louvers let you direct airflow both horizontally and vertically. You can cool the room evenly or concentrate the cool air on the spot of your choice.

### CONDENSER COIL GAURD

One of the main feature in this unit is, the fully louvered coil gaurd to protect condenser coil from dust and hail strom.